



NON API PUMPS

Mechanically Actuated Diaphragm Type Pumps

Features :

- Simple Design, Economical & Easy to maintain
- No Leakage & Low NPSHR
- Suitable for Flame Proof Area
- Wide range of plastic & Metallic MOCs



Pump Model	Strokes Lg (mm)	DIA PH DIA	SPM	Max Capacity (LPH)	Max Pressure (Kg/cm Sq)	Connection (mm)	Max Motor (KW)
DP/2/DIA/65	2	65	29	7	6.0	15	0.04
DP/2/DIA/65	2	65	48	12	6.0	15	0.04
DP/2/DIA/65	2	65	100	25	6.0	15	0.04
DP/2/DIA/65	2	65	145	37	6.0	15	0.06
DP/2/DIA/65	2	65	193	50	6.0	15	0.06
DP/3/DIA/85	3	85	29	15	6.0	15	0.04
DP/3/DIA/85	3	85	48	25	6.0	15	0.04
DP/3/DIA/85	3	85	100	50	6.0	15	0.04
DP/3/DIA/85	3	85	145	75	6.0	15	0.06
DP/3/DIA/85	3	85	193	100	6.0	15	0.06
DP/3/DIA/85	3	85	290	150	6.0	15	0.09
DP/8/DIA/80	8	80	49	84	8.0	15	0.37
DP/8/DIA/80	8	80	98	168	8.0	15	0.37
DP/8/DIA/80	8	80	147	252	8.0	25	0.37
DP/8/DIA/80	8	80	196	336	6.0	25	0.37
DP/8/DIA/90	8	90	49	108	7.3	15	0.37
DP/8/DIA/90	8	90	98	216	7.4	25	0.37
DP/8/DIA/90	8	90	147	324	7.0	25	0.37
DP/8/DIA/90	8	90	196	433	4.4	25	0.37
DP/8/DIA/100	8	100	49	138	5.6	15	0.37
DP/8/DIA/100	8	100	98	275	5.7	25	0.37
DP/8/DIA/100	8	100	147	413	5.4	25	0.37
DP/8/DIA/100	8	100	196	550	3.3	25	0.75
DP/8/DIA/120	8	120	49	189	3.4	25	0.37
DP/8/DIA/120	8	120	98	378	3.5	25	0.37
DP/8/DIA/120	8	120	147	567	3.3	25	0.75
DP/8/DIA/120	8	120	196	756	1.8	25	0.75
DP/8.5/DIA/130	8.5	130	49	247	8.0	25	0.75
DP/8.5/DIA/130	8.5	130	98	494	7.8	25	0.75
DP/8.5/DIA/130	8.5	130	147	741	7.1	25	0.75
DP/8.5/DIA/130	8.5	130	196	988	6.0	40	0.75
DP/8.5/DIA/150	8.5	150	49	323	7.5	25	0.75
DP/8.5/DIA/150	8.5	150	98	645	5.5	25	0.75
DP/8.5/DIA/150	8.5	150	147	968	4.9	40	0.75
DP/8.5/DIA/150	8.5	150	196	1290	4.2	40	1.1
DP/8.5/DIA/170	8.5	170	49	500	5.5	40	0.75
DP/8.5/DIA/170	8.5	170	98	1000	4.0	40	0.75
DP/8.5/DIA/170	8.5	170	147	1500	3.5	40	1.1
DP/8.5/DIA/170	8.5	170	196	2000	2.9	40	1.1